



Aranet MINI Datasheet

Aranet MINI

Maximum sensor count	12	
Barometer	Built in	
Alarm type	Built in audio alarm	
Memory	10+ years with 12 sensors	
Receiver sensitivity	-130 dBm	
Channels	Channel 1: 868,85 MHz	
	Channel 2: 869,05 MHz	
Graph range	Temperature	-40°C to 120°C / -40°F to 248°F
	Humidity	0% to 100%
	Pressure	280 hPa to 1050 hPa
Data resolution	Temperature	0,1°C/ 32.18°F
	Humidity	1%
	Pressure	1 hPa
Data Protection	Password for settings screen, encryption for data	
Communication	USB cable to PC	
Power options	AC Power adapter	
	USB cable from PC	
	Built in battery (backup power up to 8h)	
Operating temperature	0°C to 40°C/32°F to 104°F	
Operating humidity	0% to 100% non-condensing	
Interface languages	English, French, German, Spanish, Portuguese, Latvian	
Display	480x272 px, 4.3 inch, resistive	
Dimensions	79x137x27 mm / 3.11x5.4x1.06 in w/o stand	
Ports	2 USB micro B	
Weight	180 g/ 6.4 oz w/o stand	
Construction	ABS Plastic	
Protection class	IP40	
CE Marking	Yes	
Included	AC power adapter with USB cable, stand, Aranet PC software	
Additional	Can be used as a Monitor for Aranet PRO	

Terms of use The Customer is obliged to guarantee the usage, maintenance and preservation of the Equipment at their own expense in a way that excludes the Equipment's theft, loss, destruction, harming and/or damaging (including as a result of mechanical damages, moisture, liquid related damages, lightning and/or other similar events). Gateway may only be used indoors, it needs to be protected from environmental impact (snow, rain, direct sunlight).